



		48" Dia. Flat Top W/30"	60" Dia. Flat Top W/30"	72" Dia. Flat Top W/30"
A	Overall Thickness	10"	12-3/4"	13"
B	Slab Thickness	6"	8"	8"
C	Outside Diameter	58"	72"	86"
D	Rebar	#4 Bar @6"O.C.E.W.	#4 Bar @6"O.C.E.W.	#4 Bar @6"O.C.E.W.
E	Wire In Walls	.277 Wire @6"O.C.	.277 Wire @4-3/4"O.C.	.277 Wire @3-3/4"O.C.
	Weight	1340#	2620#	4120#

		84" Dia. Flat Top W/30"
A	Overall Thickness	13"
B	Slab Thickness	8"
C	Outside Diameter	100"
D	Rebar	#4 Bar @6"O.C.E.W.
E	Wire In Walls	.277 Wire @3-1/4"O.C.
	Weight	5520#

Notes:

1. Concrete 4,000 P.S.I. Min.
2. Constructed As Per ASTM C-478.
3. Butyl Joints Meet ASTM-C990.
4. All Rebar Meets ASTM A-615, Grade 60.
5. Reinforcing Wire Meets ASTM A-82.

Type of Coating: _____ Interior ___ Exterior ___.